



T SERIES, MODULAR BEACON, Ø75MM

859515405

TDF BLUE LED Multi Strobe 24VAC/DC

- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range



PRODUCT DESCRIPTION

AUER's T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

SPECIFICATIONS

Color Lens	Blue
Diameter	75 mm
Flash Frequency	1 Hz
Height	75 mm
IK Class	8
IP Class	IP66
Light source	LED
Light type	Multi strobe
Mounting	Bayonet
Nominal current	250 mA

Nominal Supply Voltage 24 V AC/DC

Operational Temperature -30°C ... 60°C

Terminal connection 2.5 mm²

Weight 86 g

