



## T SERIES, MODULAR BEACON, Ø75MM

859514313

LED Multi-strobe, Ø75mm, Clear, 230-240 V ac, TDF

- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range



### PRODUCT DESCRIPTION

AUERs T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

### SPECIFICATIONS

|                 |              |
|-----------------|--------------|
| Color Lens      | Clear        |
| Diameter        | 75 mm        |
| Flash Frequency | 1 Hz         |
| Height          | 75 mm        |
| IK Class        | 8            |
| IP Class        | IP66         |
| Light source    | LED          |
| Light type      | Multi strobe |
| Mounting        | Bayonet      |
| Nominal current | 42 mA        |

