

U SERIES, MODULAR BEACON, Ø60M

858511405 UDF AMBER LED MULTI STROBE 24VAC/DC

- Ø60mm, Modular beacon
- Steady, Flashing and Multi-strobe light options
- Wide control voltage range



PRODUCT DESCRIPTION

AUERs U Series range begins with a Ø 65 mm comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a Steady beacon option with base integrated BA15d socket for 4 W incandescent bulb, the U Series can be used for a range of applications involving industrial and general applications. It is fir for plc applications like leakage and inrush current. And has a UL type of 4/4X/13.

SPECIFICATIONS

| Color Lens | Orange |
|------------------------|--------------|
| Diameter | 60 mm |
| Flash Frequency | 1 Hz |
| Height | 58 mm |
| IK Class | 8 |
| IP Class | IP66 |
| Light source | LED |
| Light type | Multi strobe |
| Mounting | Bayonet |
| Nominal current | 120 mA |
| Nominal Supply Voltage | 24 V AC/DC |

| Number Of Optional Modules | 1 |
|----------------------------|---------------------|
| Operational Temperature | -30°C 60°C |
| Terminal connection | 2.5 mm ² |
| Weight | 52 g |

