



## U SERIES, MODULAR BEACON, Ø60M

858512310

UDF RED LED STROBE 110/120VAC/DC

- Ø60mm, Modular beacon
- Steady, Flashing and Multi-strobe light options
- Wide control voltage range



### PRODUCT DESCRIPTION

AUER's U Series range begins with a Ø 65 mm comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a Steady beacon option with base integrated BA15d socket for 4 W incandescent bulb, the U Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13.

### SPECIFICATIONS

Color Lens	Red
Diameter	60 mm
Flash Frequency	1 Hz
Height	58 mm
IK Class	8
IP Class	IP66
Light source	LED
Light type	Multi strobe
Mounting	Bayonet
Nominal current	33 mA
Nominal Supply Voltage	110-120 V AC

Number Of Optional Modules	1
Operational Temperature	-30°C ... 60°C
Terminal connection	2.5 mm <sup>2</sup>
Weight	52 g

