

SIGNAL TOWER Ø 40MM ECO

ECO40-Q81

Eco40mm compl green, red, amber + summer



- · Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
 - LED steady/LED strobe and LED multi strobe modules
 - Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
 - Piezo buzzer and multi tone siren modules
 - Easy to wire connections
 - Comprehensive range of mounting options including quick mount solutions
 - Plc fit (leakage and inrush current)
 - High ingress protection IP 66 certified to UL type 4/4X/13

SPECIFICATIONS

Diameter	40 mm
IP Class	IP66
Mounting	Bayonet

Operating Voltage AC Max	253 V AC
Operating Voltage AC Min	207 V AC
Supply Voltage	230 V







