



## SIGNAL TOWER Ø 70MM ECO

ECO70-Q02

signal tower Eco70mm complete green, red

- Modular signal tower
- Integrated LED or filament bulb
- Wide control voltage range



### PRODUCT DESCRIPTION

The ECO range of modular signal towers uses the highest quality components and the latest technology but at an affordable price,

- Modular signal tower series in diameters Ø 70 mm, 60 mm and 40 mm for universal applications
- Modern signal tower concept based on up-to-date LED technique, alternative operation with conventional incandescent bulb technique
- Excellent cost/performance ratio
- Complete range of bright LED modules in function modes
- LED steady light
- LED flashing light
- LED strobe light (single flash)
- LED multi strobe light (multi flash)
- LED steady/LED strobe and LED multi strobe modules
- Very long lifetime due to maintenance free LED technique, vibration proof and significantly reduced nominal current
- Piezo buzzer and multi tone siren modules
- Easy to wire connections
- Comprehensive range of mounting options including quick mount solutions
- Plc fit (leakage and inrush current)
- High ingress protection IP 66 certified to UL type 4/4X/13

### SPECIFICATIONS

<b>Color Lens</b>	Green, Red
<b>IP Class</b>	IP66
<b>Light source</b>	LED
<b>Mounting</b>	Bayonet
<b>Number Of Optional Modules</b>	2
<b>Supply Voltage</b>	24 V

Temperature range from -30 °C

Temperature range to 60 °C









