




PICK-OFF TERMINALS AND TEST ADAPTERS

MAG, SMAG, STA, TA, ZTA

2822.0 TAD 6/1/S, Test adaptor for RKD4

- STA, SMAG compatible with SRK series
- SMAG extends standard feed-through terminal up to 4 connections
- STA test adapters for SRK series
- TA test adapters dfor RK series
- ZTA Test adaptors for ZIZA/ZRK series



PRODUCT DESCRIPTION

CONTA-CLIP offers specific and innovative accessories for the SRK I SSL screw connection system.

Pick-off terminals SMAG

- The SMAG pick-off terminals make possible one or two additional extra wire connectors onto the SRK terminal blocks and therefore extend the standard feed-through terminal by up to four connectors.
- The SMAGs are mechanically snapped into the SRK terminal blocks.
- The SMAG busbar is connected via the corresponding base connection of the terminal block, the rated cross section is thereby reduced to the next lower size.

Test adapter STA

- The ST test adapter can be used to quickly and safely test pre-wired terminal blocks.
- A test plug block can be mounted with any number of poles using the locking pegs and the STA ZP intermediate plate with widths from 1 to 3 mm. The STA ZP intermediate plate allows the assembly of a test plug block, which can also be mounted on different block widths (SRK/SSL 2.5 | 4 | 6 | 10).
- Thanks to its innovative design the STA test adapter can be rotated through 180°. It can therefore also be mounted onto the SRK terminal block, whereby one of the cross-connection channels is already occupied by a cross-connector.

 | Thanks to its innovative design the STA test adapter can be rotated through 180°. It can therefore also be mounted onto the SRK terminal block, whereby one of the cross-connection channels is already occupied by a cross-connector.

SPECIFICATIONS

Additional information	for RKD 4 on screw
Color	Beige
Country of origin	DE
Cross section stranded wire from	0.5 mm²
Cross section stranded wire to	1 mm²
Flamklass	UL94-V2
Insulation Material	Polyamide 6.6
Length	37.3 mm
Operating temperature from	-40 °C
Operating temperature to	105 °C
Pack Size	10
Pitch	6 mm
Stripping Length	5 mm
Tariff code	85369010
Weight	10 g