

FEED THROUGH TERMINALS - RK 2.5-240MM²

RK

1120.2

RK 50 Beige, 50mm² Feed through terminal, multi-foot

- Screw in cross connectors
- Material polyamide 6.6 - UL94-V2
- Various colour options
- Temperature resistance -40 °C...+105 °C
- Multi-foot TS35/TS32 options



PRODUCT DESCRIPTION

SPECIFICATIONS

Additional information	with housing pegs and allen screws
Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Banded wire up to	11.8 x 5.0 mm
Color	Beige
Connections	2
Contamination degree	3
Country of origin	CZ
Cross section single wire from	16 mm ²
Cross section single wire to	50 mm ²
Cross section stranded wire from	25 mm ²
Cross section stranded wire to	50 mm ²
Cross section stranded with ferrule from	25 mm ²
Cross section stranded with ferrule to	50 mm ²
Cross-Section	50 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059

EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2
GL test standard	IEC 60947-7-1:2002
Height TS 32	82 mm
Height TS 35/7.5	76,5 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	79 mm
Mounting	TS 35/7,5 and TS 32
Number of levels	1
Operating temperature from	-40 °C
Operating temperature to	105 °C
Overvoltage category	III
Pack Size	10
Plug gauge acc. EN 60 947-1	B10
Rated Current CSA	150 A
Rated current CSAus	150 A
Rated Current IEC	150 A
Rated Current To UL	150 A
Rated impulse voltage	8 kV
Rated wire cross section from (AWG)	6
Rated wire cross section to (AWG)	1/0
Rated voltage CSAus	600 V
Rated Voltage IEC	1000 V
Rated Voltage To UL	600 V
Screw size	M 6
Screw type	Hexagon/Allen key
Stripping Length	27 mm
Tariff code	85369010
Torque max	6
Torque Min	3
Type of terminal	Screw Terminals, DIN Rail terminals
UL test standard	UL 1059
Weight	123,6 g

Width	20 mm
Voltage CSA	600 V

