

DOUBLE DECK TERMINALS - RKD 2.5-4MM²

RKD, RKDG

2584.2

RKDG 4 Beige, 4mm² Double deck, same level

- Screw cross connectors
- Temperature resistance -40 °C...+105 °C
- Polyamide 6.6 UL94-V2
- Same level screw option
- Versions with electronic components fitted



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	KEMA KUR
Color	Beige
Connections	2 x 2
Contamination degree	3
Country of origin	DE
Cross connect channels	1
Cross section single wire from	0,2 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0,2 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0,2 mm ²
Cross section stranded with ferrule to	4 mm ²
Cross-Section	4 mm ²
Flamklass	UL94-V2
Height TS 35/7.5	60 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	58,5 mm

Mounting	TS 35/7,5
Number of levels	2
Operating temperature from	-40 °C
Operating temperature to	105 °C
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A4
Rated Current IEC	32 A
Rated impulse voltage	6 kV
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	12
Rated Voltage IEC	500 V
Screw size	M 3
Screw type	Slotted
Stripping Length	9 mm
Tariff code	85369010
Torque max	1
Torque Min	0,5
Type of terminal	Screw Terminals, DIN Rail terminals
Weight	16,06 g
Width	6 mm