


FEED THROUGH TERMINALS - ZRK 2.5-16 MM²

ZRK

3504.2

ZRK 2,5/2x2A/D1 Beige, 2.5mm² Tension spring with Diode

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, CSA US, KEMA KUR, EAC
Color	Beige
Connections	2 x 2
Contamination degree	3
Country of origin	BG
Cross connect channels	1
Cross section single wire from	0.5 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.5 mm ²
Cross section stranded wire to	4 mm ²

Cross section stranded with ferrule from	0.5 mm ²
Cross section stranded with ferrule to	2.5 mm ²
Cross-Section	2.5 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
Diode type	1N4007 / 1000V / 1A
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V0
Height TS 35/7.5	39 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	83.6 mm
Mounting	TS 35/7,5
Number of levels	1
Number of test pick off options	2
Operating temperature from	-40 °C
Operating temperature to	120 °C
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A3
Rated Current CSA	27 A
Rated current CSAus	27 A
Rated Current IEC	24 A
Rated Current To UL	1 A
Rated impulse voltage	8 kV
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	12
Rated voltage CSAus	600 V
Rated Voltage IEC	800 V
Rated Voltage To UL	600 V
Stripping Length	10 mm
Tariff code	85369010
UL test standard	UL 1059

Weight	11 g
Width	5.1 mm
Voltage CSA	600 V

