


EARTH TERMINALS - ZSL 2.5-16MM²

ZSL

3525.2
ZSL 4/2A GNYE

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, GL, CSA US, cUL, KEMA KUR, EAC
Color	Green/yellow
Connections	2
Contamination degree	3
Country of origin	CZ
Cross connect channels	0
Cross section single wire from	0.5 mm ²
Cross section single wire to	6 mm ²
Cross section stranded wire from	0.6 mm ²
Cross section stranded wire to	6 mm ²
Cross section stranded with ferrule from	0.5 mm ²
Cross section stranded with ferrule to	4 mm ²
Cross-Section	4 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V0
GL test standard	IEC 60947-7-2:2009
Height TS 35/7.5	42 mm

Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-2:2009
Length	64 mm
Mounting	TS 35/7,5
Number of levels	1
Number of test pick off options	2
Operating temperature from	-40 °C
Operating temperature to	120 °C
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A4
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	10
Stripping Length	12 mm
Tariff code	85369010
UL test standard	UL 1059
Weight	14.8 g
Width	6.1 mm

