


DOUBLE DECK TERMINALS - ZRKD 2.5MM²

ZRKD

3562.2
ZRKD 2,5 BG

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Color	Beige
Connections	2 x 2
Contamination degree	3
Country of origin	CZ
Cross connect channels	2
Cross section single wire from	0.5 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.5 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0.5 mm ²
Cross section stranded with ferrule to	2.5 mm ²
Cross-Section	2.5 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V0
GL test standard	IEC 60947-7-1:2009

Height TS 35/7.5	53 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	83.6 mm
Mounting	TS 35/7,5
Number of levels	2
Number of test pick off options	4
Operating temperature from	-40 °C
Operating temperature to	120 °C
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A3
Rated Current CSA	10 A
Rated current CSAus	10 A
Rated Current IEC	24 A
Rated Current To UL	10 A
Rated impulse voltage	6 kV
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	12
Rated voltage CSAus	300 V
Rated Voltage IEC	500 V
Rated Voltage To UL	300 V
Stripping Length	10 mm
Tariff code	85369010
UL test standard	UL 1059
Weight	12.8 g
Width	5.1 mm
Voltage CSA	300 V

