

## DISCONNECT TERMINALS - ZTRK 2.5MM<sup>2</sup>

ZTRK

3603.2

ZTRK 2,5/2A/MT BG

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0
- Knife isolation



### PRODUCT DESCRIPTION

## SPECIFICATIONS

<b>Additional information</b>	with disconnect blade
<b>Approvals</b>	CSA, CSA US, KEMA KUR
<b>Color</b>	Beige
<b>Connections</b>	2
<b>Contamination degree</b>	3
<b>Country of origin</b>	CZ
<b>Cross connect channels</b>	1
<b>Cross section single wire from</b>	0.5 mm <sup>2</sup>
<b>Cross section single wire to</b>	4 mm <sup>2</sup>
<b>Cross section stranded wire from</b>	0.5 mm <sup>2</sup>
<b>Cross section stranded wire to</b>	4 mm <sup>2</sup>
<b>Cross section stranded with ferrule from</b>	0.5 mm <sup>2</sup>
<b>Cross section stranded with ferrule to</b>	2.5 mm <sup>2</sup>
<b>Cross-Section</b>	2.5 mm <sup>2</sup>
<b>CSA test standard</b>	C22.2 No 158
<b>CSAus test standard</b>	UL 1059

<b>Flamklass</b>	UL94-V0
<b>Height TS 35/7.5</b>	42.3 mm
<b>Insulation Material</b>	Polyamide 6.6
<b>KEMA KEUR test standard</b>	EN 60947-7-1:2009, EN 60947-7-3:2009
<b>Length</b>	68 mm
<b>Mounting</b>	TS 35/7,5
<b>Number of levels</b>	1
<b>Number of test pick off options</b>	2
<b>Operating temperature from</b>	-40 °C
<b>Operating temperature to</b>	120 °C
<b>Overvoltage category</b>	III
<b>Pack Size</b>	100
<b>Plug gauge acc. EN 60 947-1</b>	A3
<b>Rated Current IEC</b>	18 A
<b>Rated impulse voltage</b>	6 kV
<b>Rated wire cross section from (AWG)</b>	20
<b>Rated wire cross section to (AWG)</b>	12
<b>Rated Voltage IEC</b>	400 V
<b>Stripping Length</b>	10 mm
<b>Tariff code</b>	85369010
<b>Weight</b>	9.82 g
<b>Width</b>	5.1 mm

