

COMPACT TERMINALS FOR TS15/TS35 RAIL - ZSRK/ZSL 2.5MM²

ZSRK, ZSLN

3599.1

ZSRK 2.5/3A/15 Green, 2.5mm² Compact tension spring, feed through, 1 in, 2 out, TS15

- Material polyamide 6.6
- Temperature resistance -40 °C...+120 °C
- Flammability class V0



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, CSA US, cUL, KEMA KUR, EAC
Color	Green
Connections	3
Contamination degree	3
Country of origin	CZ
Cross connect channels	1
Cross section single wire from	0.5 mm ²
Cross section single wire to	4 mm ²
Cross section stranded wire from	0.5 mm ²
Cross section stranded wire to	4 mm ²
Cross section stranded with ferrule from	0.5 mm ²
Cross section stranded with ferrule to	2.5 mm ²
Cross-Section	2.5 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V0

Height TS 15/5.5	34 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	52 mm
Load Current Max	24 A
Mounting	TS 15/5,5
Number of levels	1
Number of test pick off options	2
Operating temperature from	-40 °C
Operating temperature to	120 °C
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A3
Rated Current CSA	20 A
Rated current CSAus	20 A
Rated current cUL	20 A
Rated Current IEC	24 A
Rated Current To UL	20 A
Rated impulse voltage	8 kV
Rated wire cross section from (AWG)	20
Rated wire cross section to (AWG)	12
Rated voltage CSAus	300 V
Rated voltage cUL	300 V
Rated Voltage IEC	800 V
Rated Voltage To UL	300 V
Stripping Length	10 mm
Tariff code	85369010
UL test standard	UL 1059
Weight	8.06 g
Width	5.1 mm
Voltage CSA	300 V



