




## SPECIFICATIONS

<b>Additional information</b>	for SRK 4/2A
<b>Approvals</b>	EAC
<b>Color</b>	Beige
<b>Connections</b>	1
<b>Contamination degree</b>	3
<b>Country of origin</b>	DE
<b>Cross section single wire from</b>	0.2 mm <sup>2</sup>
<b>Cross section single wire to</b>	4 mm <sup>2</sup>
<b>Cross section stranded wire from</b>	0.2 mm <sup>2</sup>
<b>Cross section stranded wire to</b>	4 mm <sup>2</sup>
<b>Cross section stranded with ferrule from</b>	0.2 mm <sup>2</sup>
<b>Cross section stranded with ferrule to</b>	2.5 mm <sup>2</sup>
<b>Cross-Section</b>	2.5 mm <sup>2</sup>
<b>EAC test standard</b>	TR ZU 004/2011
<b>Flamklass</b>	UL94-V0
<b>Height</b>	26.7 mm
<b>Height TS 35/7.5</b>	53 mm
<b>Insulation Material</b>	Polyamide 6.6
<b>Length</b>	37.8 mm
<b>Load Current Max</b>	32 A
<b>Operating temperature from</b>	-40 °C
<b>Operating temperature to</b>	120 °C
<b>Overtoltage category</b>	III
<b>Pack Size</b>	10
<b>Plug gauge acc. EN 60 947-1</b>	A3
<b>Rated Current IEC</b>	24 A
<b>Rated impulse voltage</b>	8 kV
<b>Rated Voltage IEC</b>	800 V

<b>Rated wire cross section from (AWG)</b>	22
<b>Rated wire cross section to (AWG)</b>	12
<b>Screw size</b>	M 2,5
<b>Screw type</b>	Slotted
<b>Stripping Length</b>	10 mm
<b>Tariff code</b>	85369010
<b>Torque max</b>	0.8
<b>Torque Min</b>	0.4
<b>Type of terminal</b>	Screw Terminals, DIN Rail terminals
<b>Weight</b>	6.1 g
<b>Width</b>	5.9 mm

