

FEED THROUGH TERMINALS - RK 2.5-240MM²

RK

17370.2

RK 35/35 N Beige, 16mm² feed through, TS35

- Screw in cross connectors
- Material polyamide 6.6 - UL94-V2
- Various colour options
- Temperature resistance -40 °C...+105 °C
- Multi-foot TS35/TS32 options



PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	UL, CSA, GL, CSA US, cUL, KEMA KUR, EAC
Color	Beige
Connections	2
Contamination degree	3
Country of origin	CZ
Cross connect channels	1
Cross section single wire from	2.5 mm ²
Cross section single wire to	50 mm ²
Cross section stranded wire from	2.5 mm ²
Cross section stranded wire to	35 mm ²
Cross section stranded with ferrule from	2.5 mm ²
Cross section stranded with ferrule to	35 mm ²
Cross-Section	35 mm ²
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158

EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2
GL test standard	IEC 60947-7-1:2002
Height TS 35/7.5	52 mm
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	58 mm
Mounting	TS 35/7,5
Number of levels	1
Operating temperature from	-40 °C
Operating temperature to	105 °C
Overvoltage category	III
Pack Size	20
Plug gauge acc. EN 60 947-1	B9
Rated Current CSA	115 A
Rated current CSAus	115 A
Rated Current IEC	125 A
Rated impulse voltage	8 kV
Rated wire cross section from (AWG)	12
Rated wire cross section to (AWG)	2
Rated voltage CSAus	600 V
Rated Voltage IEC	800 V
Screw size	M 6
Screw type	Slotted
Stripping Length	20 mm
Tariff code	85369010
Torque max	5
Torque Min	2.5
Type of terminal	Screw Terminals, DIN Rail terminals
UL test standard	UL 1059
Weight	54.75 g
Width	16 mm
Voltage CSA	600 V

