



US-M/US-P METAL CONNECTOR

5010.328.010

US-M AD10 M10x1,0 connector


- Nickeled brass
- Waterproof and dust-tight
- Metric or PG thread
- IP40..IP65 rated



PRODUCT DESCRIPTION

US-M and US-P connectors are made from nickled brass, gasket material is either TPE or PTFE. O-ring is made of NBR, brass ferrule.

Available also in smaller quantities than listed below.




SPECIFICATIONS

Diameter	10 mm
Thread	M10x1,5 met. EN 60423
Pack Size	50
Temperature range from	-40 °C
Temperature range to	125 °C
Weight kg / 100 ± 10%	1.5
Material	Nickel-plated brass
Type	US-M

Fits to

SPR-PU-AS, SPR-PVC-AS



US-M, TIII SPR-AS

	\varnothing	l	B	C	D	SW	SW
	mm	mm	mm	mm	mm	mm	mm
5010.327.010	10	6,0	19,0	10,0	31,0	15	17
5010.327.012	14	8,5	23,0	10,0	33,0	19	21
5010.327.016	17	11,5	27,0	10,0	33,0	23	25
5010.327.020	21	15,5	31,0	10,0	33,0	27	29
5010.327.025	27	20,5	39,0	11,0	41,0	34	36
5010.327.032	36	27,5	48,0	13,0	43,0	43	45
5010.327.040	45	35,0	57,0	13,0	43,0	52	54
5010.327.050	56	45,0	70,0	14,0	49,0	63	66
5010.327.163	56	45,0	75,0	14,0	49,0	70	70