

CONTROL ENCLOSURE CC-3000

CC-3000 OHJAUSKOTELO
Customizable enclosure

- Customisable dimensions
- Extruded aluminium frame sections
- Rugged industrial design
- RAL9006
- High protection, IP65 rated



PRODUCT DESCRIPTION

Bernstein CC-3000 is a fully customized control enclosure that meets specific requirements with top quality. The product features:

- Monitor-based industrial design
- Freely selectable width and height (max. 600 x 600)
- Customised colours from RAL range
- Five possible enclosure designs
- Optimum heat dissipation due to single-walled sections
- Front panels internally-mounted or externally-mounted
- Protection class IP65
- Screw-fixed or hinged rear panel
- Rear panel attachments without restricting installation space
- Internal grooves for fixing components
- Extensive range of accessories

SPECIFICATIONS

IP Class	IP65
Temperature range from	-30 °C
Temperature range to	80 °C
Color	Grey
Material	Aluminium



Single section configuration

Front panel	Rear panel	Section depth	Installation depth
A Internally mounted	Fixed or hinged	120	103
		200	183
B Externally mounted	Fixed or hinged	120	111
		200	191



Aluminium section depth comparison: 200 mm (left) and 120 mm (right)

Single section configuration

Front panel	Rear panel	Section depth	Installation depth
A Internally mounted	Fixed or hinged	120	103
		200	183
B Externally mounted	Fixed or hinged	120	111
		200	191



Aluminium section depth comparison: 200 mm (left) and 120 mm (right)

Configuration with combination of two sections (as door)

Front panel	Rear panel	Section depth	Installation depth
C Internally mounted	Internally mounted	120+55	149
		200+55	229
D Externally mounted	Internally mounted	120+55	157
		200+55	237
E Internally mounted	Externally mounted	120+55	157
		200+55	237
F Externally mounted	Externally mounted	120+55	166
		200+55	246



120 mm section with additional door extension (55 mm)

Configuration with combination of two sections (as door)

Front panel	Rear panel	Section depth	Installation depth
C Internally mounted	Internally mounted	120+55	149
		200+55	229
D Externally mounted	Internally mounted	120+55	157
		200+55	237
E Internally mounted	Externally mounted	120+55	157
		200+55	237
F Externally mounted	Externally mounted	120+55	166
		200+55	246



120 mm section with additional door extension (55 mm)