BERNSTEIN

CONTROL ENCLOSURE CC-5000

CC-5000 OHJAUSKOTELO
Customizable enclosure



- Customisable dimensions
- Extruded aluminium frame sections
- Rugged industrial design
- RAL9006
- High protection, IP65 rated

PRODUCT DESCRIPTION

Custom versions can be supplied to meet individual customer specifications. The product features:

- Innovative and modern industrial design
- Rounded edges, no risk of physical injury
- High-quality extruded aluminium sections (naturally anodised)
- Customised colours from RAL range
- Single-walled sections that provide outstanding heat dissipation
- Integrated recessed grips for simple handling
- Protection class IP65
- Operating temperature -30 °C to +80 °C
- Internally mounted front panel
- Door configurations for direct access to the interior
- Slimline design for configuring flat screen systems

SPECIFICATIONS

IP Class	IP65

Temperature range from	-30 °C
Temperature range to	80 °C
Color	Grey
Material	Aluminium













Basis sections	External depth	Installation depth
	75 mm	53 mm
	125 mm	103 mm
	185 mm	163 mm
Section combinations	**External depth**	**Installation depth**
	150 mm (75 + 75)	114 mm
	200 mm (75 +125 or 125 + 75)	164 mm
	250 mm (125 + 125)	214 mm
	260 mm (75 + 185 or 185 + 75)	224 mm
	310 mm (125 + 185 or 185 + 125)	274 mm
	370 mm (185 + 185)	334 mm

Basis sections	External depth	Installation depth
	75 mm	53 mm
	125 mm	103 mm
	185 mm	163 mm
Section combinations	**External depth**	**Installation depth**
	150 mm (75 + 75)	114 mm
	200 mm (75 +125 or 125 + 75)	164 mm
	250 mm (125 + 125)	214 mm
	260 mm (75 + 185 or 185 + 75)	224 mm
	310 mm (125 + 185 or 185 + 125)	274 mm
	370 mm (185 + 185)	334 mm