

NH FUSE-LINKS NH00, AM

500 V AC, 690 V AC

NH00AM69V80

NH fuse-link NH00 aM 690 V 80 A

- Size 00
- Silver-plated copper contacts
- Ceramic body
- Breaking capacity 80 kA



PRODUCT DESCRIPTION

Mersen/Ferraz Shawmut gG type NH fuses are suitable for protecting motor circuits. Partial range breaking capacity. Suitable for short-circuit protection only, interrupts current from 6,3 x In up to maximum breaking capacity. They must be associated with other switchgear for protection against overloads. These fuse-links can have a rated current equal to the motor's nominal current.

Characteristics

- Dimensions according to DIN 43 620 Parts 1 to 4
- Non-Isolated metal gripping slugs
- Double indicator
- Lead-free connectors
- 0% cadmium

SPECIFICATIONS

| | |
|-----------------------------|--|
| Approvals | BV, CB, CE, DNV, KEMA KEUR, Lloyd's, VDE |
| Breaking Capacity | 80 kA |
| Characteristic (CVL) | aM |
| Indication (CVL) | Visual, Striker |
| Manufacturer Part No | F227866 |
| Nominal current | 80 A |
| Pack Size | 3 |
| Voltage AC max | 690 V |

