

## NH FUSE-LINKS NH000, AM

500 V AC, 690 V AC

NH000AM50V35

NH fuse-link NH000 aM 500 V 35 A

- Size 000
- Silver-plated copper contacts
- Ceramic body
- Breaking capacity 80/120 kA



### PRODUCT DESCRIPTION

Mersen/Ferraz Shawmut gG type NH fuses are suitable for protecting motor circuits. Partial range breaking capacity. Suitable for short-circuit protection only, interrupts current from 6,3 x In up to maximum breaking capacity. They must be associated with other switchgear for protection against overloads. These fuse-links can have a rated current equal to the motor's nominal current.

#### Characteristics

- Dimensions according to DIN 43 620 Parts 1 to 4
- Non-Isolated metal gripping slugs
- Double indicator
- Lead-free connectors
- 0% cadmium

### SPECIFICATIONS

|                             |  |
|-----------------------------|--|
| <b>Approvals</b>            | BV, CB, CE, DNV, KEMA KEUR, Lloyd's, VDE |
| <b>Breaking Capacity</b>    | 120 kA                                   |
| <b>Characteristic (CVL)</b> | aM                                       |
| <b>Indication (CVL)</b>     | Visual, Striker                          |
| <b>Manufacturer Part No</b> | T232501                                  |
| <b>Nominal current</b>      | 35 A                                     |
| <b>Pack Size</b>            | 3  |
| <b>Voltage AC max</b>       | 500 V                                    |

