

IEC FUSE HOLDER MODULOSTAR®

CMC 10 (10x38)

CMC103NI

IEC Fuse holder 3+N (10x38) + ind.

- DIN rail mounting
- Optional visual blown fuse indicator
- Shock and vibration tested for marine and railway applications



PRODUCT DESCRIPTION

Mersen ModuloStar® series offer wide variety of fuse holders. Easy fuse changing, IP20 rated. 1, 2, 3 or 4 pole versions available. Optional blown fuse indicator.

- IP20 rated
- Available with or without an indicator
- DIN rail mounting
- Modular
- Sealable in open or closed position
- Shock and vibration resistant

New ModuloStar CMC10 replace old ModuloStar CMS10 fuse holders.

NEW			OLD	
Reference	Description	Catalog number	Old ref	old cat nb
P1062705	MODULOSTAR CMC10 1P	CMC101	T305020	CMS101
G1062698	MODULOSTAR CMC10 1P+N	CMC101N	V305021	CMS101N
H1062699	MODULOSTAR CMC10 2P	CMC102	W305022	CMS102
E1062696	MODULOSTAR CMC10 3P	CMC103	X305023	CMS103
Y1062690	MODULOSTAR CMC10 3P+N	CMC103N	Y305024	CMS103N
Z1062691	MODULOSTAR CMC10 4P	CMC104	Z305025	CMS104
S1062708	MODULOSTAR CMC10 1P C/I	CMC101I	A305026	CMS101I
J1062700	MODULOSTAR CMC10 1P+N C/I	CMC101NI	B305027	CMS101NI
L1062702	MODULOSTAR CMC10 2P C/I	CMC102I	C305028	CMS102I
F1062697	MODULOSTAR CMC10 3P C/I	CMC103I	D305029	CMS103I
A1062692	MODULOSTAR CMC10 3P+N C/I	CMC103NI	E305030	CMS103NI

SPECIFICATIONS

Approvals	BV, CB, CCC, CE, GL, Lloyd's, REACH, RoHS
Breaking capacity max	200 kA
Current max	32 A
Indication (CVL)	Visual
Manufacturer Part No	A1062692
Material	PVC
Number of poles	4
Pack Size	3
Width	70 mm
Voltage AC max	690 V
Voltage DC max	690 V

