

ENCLOSURE LIGHTING - LED 025 ECOLINE

Ecoline

02540.1-10

LED 025 Eco, 24-48V dc, with on/off switch, magnetic

- LED long lifetime
- Externally switched version
- Wide AC/DC voltage range
- Quick connect spring terminals



PRODUCT DESCRIPTION

LED025 ECOLINE is a LED light from STEGO with quick connection through spring clamp.

LED025 ECOLINE can be used for all types of panel or cabinet installations, but is particularly good when space is limited due to its optimal size. The lighting has a very long life due to LED technology, which results in savings in service and maintenance.

LED025 ECOLINE is available in three different mounting options to suit different applications:

Magnetic assembly, which can be mounted very quickly and can be moved around the cabinet if necessary.

Screw mounting, for "traditional" mounting.

Clip assembly, which is a type of screw mounting, but where the lighting can be angled and also easily moved as needed.

LED025 ECOLINE has the same luminance as a 95W bulb, but consumes only 5 W.

LED025 ECOLINE is available with both 100-240 V AC and 90-110 V DC in one and the same unit, which makes it easy for both purchases and storage.

SPECIFICATIONS

Activation	Switch
Approvals	CE, cULus, EAC, RoHS, UL, UL E234324, VDE
Color	Transparent
Height	34 mm
Humidity Storage	<90% RH
IP Class	IP20
Length	351 mm
Light source	LED
Material of body	Plastic
Mounting	Magnetic mount
Nominal voltage	24-48 V DC
Operating Humidity	< 90% RH

Operational Temperature	-30°C ... +60°C
Power Consumption	5 W
Protection Class	II (double insulated)
Storage temperature	-40°C ... +85°C
Weight	0.2 kg
Width	32 mm
Voltage max	60 V dc
Voltage min	20 V dc

