

## NGFLGÖU-J UNSHIELDED RUBBER FLAT CABLE

KAB003008015/04  
NGFLGÖU-J 8G1,5 mm<sup>2</sup>



- Particularly for hoists and cranes
- Applicable in dry, damp and wet conditions
- Resistant against oil, ozone and UV light

### PRODUCT DESCRIPTION

Feeder and control cable especially constructed for hoists, transport equipment and cranes. Withstands medium mechanical stress and is applicable in dry, damp and wet conditions.

### SPECIFICATIONS

Number Of leads	8
Cross-Section	1.5 mm <sup>2</sup>
Material Outer Jacket	Rubber compound
Shielded	No
Nominal Voltage	U <sub>o</sub> /U 300/500 V
Temperature Range The Use Of	-40 °C
Temperature Range For Flexible Use	80 °C
Temperature Range Flexible Use Of	-35 °C
Bending Radius Fixed Laying	5 x d
Bending Radius Flexible Use	5 x d
Copper Weight	115 kg/km
Weight	310 kg/km
Core Insulation	Rubber compound
Core identification	Number Coded
Approvals	RoHS
Test Voltage	2000 V
Area of application	Flexible use
Colour Outer Sheath	Black
Cable type	Hi-flex cable

**RRRC**