

## YSLY PVC CONTROL CABLE

SAB02001805/04K  
 YSLY-JZ 18G0,5 mm<sup>2</sup>

- Cable fit for multitude of applications
- Flexible
- Small bend radius



### PRODUCT DESCRIPTION

YSLY PVC cable fits excellently in various indoors applications as power or control cable. Can be used for example in conveyor belts, packaging machines, machining tools and wood working machinery.

### SPECIFICATIONS

|                                    |                             |
|------------------------------------|-----------------------------|
| Number Of leads                    | 18                          |
| Cross-Section                      | 0.5 mm <sup>2</sup>         |
| Material Outer Jacket              | PVC                         |
| Shielded                           | No                          |
| Nominal Voltage                    | U <sub>0</sub> /U 300/500 V |
| Rated voltage U <sub>0</sub> / U   | 300/500                     |
| Diameter Outer -5%                 | 11.8 mm                     |
| Temperature Range The Use Of       | -40 °C                      |
| Temperature Range For Flexible Use | 80 °C                       |
| Temperature Range Flexible Use Of  | -5 °C                       |
| Bending Radius Fixed Laying        | Min. 7,5 x d                |
| Bending Radius Flexible Use        | Min. 7,5 x d                |
| Copper Weight                      | 86 kg/km                    |
| Weight                             | 195 kg/km                   |
| Core Insulation                    | PVC                         |
| Core identification                | Number Coded                |
| Approvals                          | RoHS                        |
| Test Voltage                       | 4000 V                      |
| Area of application                | Flexible use                |

---

**Colour Outer Sheath**

Grey

---