

## HMH/HMH-EB HALOGEN-FREE CONTROL CABLE

**<b>©**EM AUTOMATIC

SAB62000560/04K HMH-JZ 5G6 mm<sup>2</sup>

1	П	ı	İ	I	İ	ĺ	ı	ı	ĺ	ı	ı	ĺ	ĺ	ı	ı	ĺ	ĺ	ı	ľ	ı	ı	Ì	ľ	I	ı	ı	İ	ı	ı	ı	ı	ı	Ì	ľ	ı	ı	ı	ı	ľ	ı	ı	ı	Ì	ı	ı	ı	ľ	II	II	ı	İ	ı	ı	II	ı	ı	II	ı	ı	II	ı	ı	Ħ	ı	ı	ľ	ľ	ľ	II	ı	ľ	ľ	ı	ı	ı	II	H
ı					ı																																																									l															
н		ı	Ш	II	ı	Ш		ı	Ш		u	l	Ш	II	ı	Ш	Ш	ı	ı	I	ı	l	Ш	Ш	ı	ı	l	Ш	Ш	Ш	ı	ı	l	Ш	u	u	ı	l	l	Ш	u	ı	l	Ш	u	ı	ı	Ш		ı	l	Ш	ı	Ш	u	ı	Ш	u	ı	Ш	ı	l	Ш	Ш	u	l	Ш	Ш	u	u	ı	Ш	II	u	ı	Ш	Ш

- Numbered cores
- Flame retardant and self-extinguishing
- Flexible
- · Easy stripping

## PRODUCT DESCRIPTION

HMH/HMH-EB is a halogen-free control cable constructed for use as control, measuring and monitoring cable in multitude of applications such as assembly lines and conveyor belts. Suitable for dry and damp environments as well as areas prone to fire.

## **SPECIFICATIONS**

Number Of leads	5
Cross-Section	6 mm²
Material Outer Jacket	LSZH
Shielded	No
Nominal Voltage	Uo/U 300/500 V
Diameter Outer -5%	15.8 mm
Temperature Range The Use Of	-40 °C
Copper Weight	442 kg/km
Weight	442 kg/km
Core identification	Number Coded
Approvals	RoHS
Halogen	Yes
Halogen free	Yes
Colour Outer Sheath	Grey

