

HMH/HMH-EB HALOGEN-FREE **CONTROL CABLE**

SAB62001807/04K HMH-JZ 18G0,75 mm²

1	ı	I	ı	İ	ı	I	I	I	ı	I	I	ı	I	ı	I	ı	ı	I	ı	I	ı	I	ı	I	I	ı	I	ı	I	ı	ı	I	ı	I	I	ı	ı	I	I	I	I	ı	I	I	I	ı	ı	I		ı	ı
	ı	l			ı	l			ı			ı	l	l			l		ı	ı		l	ı			ı	l	ı			ı		ı			ı	l		l		l	ı	l				l	ı		ı	ı

©EM AUTOMATIC

- Numbered cores
- Flame retardant and self-extinguishing
- Flexible
- · Easy stripping

PRODUCT DESCRIPTION

HMH/HMH-EB is a halogen-free control cable constructed for use as control, measuring and monitoring cable in multitude of applications such as assembly lines and conveyor belts. Suitable for dry and damp environments as well as areas prone to fire.

SPECIFICATIONS

Number Of leads	18
Cross-Section	0.75 mm²
Material Outer Jacket	LSZH
Shielded	No
Nominal Voltage	Uo/U 300/500 V
Diameter Outer -5%	14 mm
Temperature Range The Use Of	-40 °C
Copper Weight	249 kg/km
Weight	249 kg/km
Core identification	Number Coded
Approvals	RoHS
Halogen	Yes
Halogen free	Yes
Colour Outer Sheath	Grey

