

NGFLGÖU-J UNSHIELDED RUBBER FLAT CABLE

KAB003004015/04
 NGFLGÖU-J 4G1,5 mm²



- Particularly for hoists and cranes
- Applicable in dry, damp and wet conditions
- Resistant against oil, ozone and UV light

PRODUCT DESCRIPTION

Feeder and control cable especially constructed for hoists, transport equipment and cranes. Withstands medium mechanical stress and is applicable in dry, damp and wet conditions.

SPECIFICATIONS

Number Of leads	4
Cross-Section	1.5 mm ²
Material Outer Jacket	Rubber compound
Shielded	No
Nominal Voltage	U ₀ /U 300/500 V
Temperature Range The Use Of	-40 °C
Temperature Range For Flexible Use	80 °C
Temperature Range Flexible Use Of	-35 °C
Bending Radius Fixed Laying	5 x d
Bending Radius Flexible Use	5 x d
Copper Weight	58 kg/km
Weight	160 kg/km
Core Insulation	Rubber compound
Core identification	Colour Coded
Approvals	RoHS
Test Voltage	2000 V
Area of application	Flexible use
Drag Chain Tested	No
Colour Outer Sheath	Black
Cable type	Hi-flex cable

RoHS ✓ RoHS ✓