

NGFLGÖU-J UNSHIELDED RUBBER FLAT CABLE

KAB003012015/04

NGFLGÖU-J 12G1,5 mm²


- Particularly for hoists and cranes
- Applicable in dry, damp and wet conditions
- Resistant against oil, ozone and UV light

PRODUCT DESCRIPTION

Feeder and control cable especially constructed for hoists, transport equipment and cranes. Withstands medium mechanical stress and is applicable in dry, damp and wet conditions.

SPECIFICATIONS

| | |
|------------------------------------|-----------------------------|
| Number Of leads | 12 |
| Cross-Section | 1.5 mm ² |
| Material Outer Jacket | Rubber compound |
| Shielded | No |
| Nominal Voltage | U _o /U 300/500 V |
| Temperature Range The Use Of | -40 °C |
| Temperature Range For Flexible Use | 80 °C |
| Temperature Range Flexible Use Of | -35 °C |
| Bending Radius Fixed Laying | 5 x d |
| Bending Radius Flexible Use | 5 x d |
| Copper Weight | 173 kg/km |
| Weight | 510 kg/km |
| Core Insulation | Rubber compound |
| Core identification | Number Coded |
| Approvals | RoHS |
| Test Voltage | 2000 V |
| Area of application | Flexible use |
| Colour Outer Sheath | Black |
| Cable type | Hi-flex cable |

RRRC