

H05RR-F FINE-STRANDED CABLE

KAB00900215/04K
H05RR-F 2x1,5 mm²



- Rubber cable for connecting electrical appliances
- Suited for medium mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Household, office and commercial applications

PRODUCT DESCRIPTION

Rubber-insulated H05RR-F is suitable for connecting various household, office and commercial electrical appliances such as vacuums, different kitchen equipment and tools. Withstands medium mechanical stress, applicable also for fixed installations.

SPECIFICATIONS

| | |
|------------------------------------|-----------------------------|
| Number Of leads | 2 |
| Cross-Section | 1.5 mm ² |
| Material Outer Jacket | Rubber compound |
| Shielded | No |
| Nominal Voltage | U _o /U 300/500 V |
| Diameter Outer -5% | 8.2 mm |
| Temperature Range The Use Of | -30 °C |
| Temperature Range For Flexible Use | 60 °C |
| Temperature Range Flexible Use Of | -30 °C |
| Bending Radius Fixed Laying | Min. 7,5 x d |
| Bending Radius Flexible Use | Min. 7,5 x d |
| Copper Weight | 43 kg/km |
| Weight | 112 kg/km |
| Core Insulation | Rubber compound |
| Core identification | Colour Coded |
| Approvals | RoHS |
| Test Voltage | 2000 V |
| Area of application | Flexible use |
| Colour Outer Sheath | Black |
| Cable type | Rubber-insulated cable |

RRRC