

## PVC 2S CONTROL AND FEEDER CABLE

KAB01801215/04

PVC 2S 12G1,5 mm<sup>2</sup>


- High tensile strength
- For dry, damp and wet environments
- Flexible also in cold environments

### PRODUCT DESCRIPTION

PVC 2S cables are suitable for use as control and feeder cables for example in lifts and conveyor belts. High resistance against wear, steel support wires for maximum tensile strength.

Flame retardant in accordance with IEC/EN 60332-1-2

### SPECIFICATIONS

|                                    |                      |
|------------------------------------|----------------------|
| Number Of leads                    | 12                   |
| Cross-Section                      | 1.5 mm <sup>2</sup>  |
| Material Outer Jacket              | PVC                  |
| Shielded                           | No                   |
| Rated voltage U <sub>0</sub> / U   | 300/500              |
| Temperature Range For Flexible Use | 70 °C                |
| Temperature Range Flexible Use Of  | -15 °C               |
| Bending Radius Fixed Laying        | Min. 14 x D          |
| Bending Radius Flexible Use        | Min. 20 x D          |
| Copper Weight                      | 173 kg/km            |
| Weight                             | 505 kg/km            |
| Core Insulation                    | PVC                  |
| Core identification                | Number Coded         |
| Approvals                          | RoHS, REACH, CE, IEC |
| Test Voltage                       | 2000 V               |
| Area of application                | Flexible use         |
| Colour Outer Sheath                | Black                |