# 2YSLCYK-J 0,6/1 KV

KAB55000415/04K
2YSLCYK-J 4G1,5 mm² 0,6/1kV



- Shielded
- Motor power supply cable
- Good EMC-properties

**PRODUCT DESCRIPTION**

2YSLCYK-J 0,6/1 kV motor power supply cable is suitable for frequency converters. In order to achieve optimal EMC-properties the copper screen has to be grounded.

## SPECIFICATIONS

| | |
|---|---|
| **Number Of leads** | 4 |
| **Cross-Section** | 1.5 mm² |
| **Material Outer Jacket** | PVC |
| **Shielded** | Yes |
| **Nominal Voltage** | Uo/U 0,6/1 kV |
| **Rated voltage U0 / U** | 0,6/1kV |
| **Diameter Outer -5%** | 10.4 mm |
| **Temperature Range The Use Of** | -40 °C |
| **Temperature Range For Flexible Use** | 70 °C |
| **Temperature Range Flexible Use Of** | -5 °C |
| **Copper Weight** | 95 kg/km |
| **Weight** | 217 kg/km |
| **Core Insulation** | PVC |
| **Core identification** | Colour Coded |
| **Approvals** | RoHS |
| **Test Voltage** | 2500 V |
| **Area of application** | Flexible use |
| **Drag Chain Tested** | No |
| **Colour Outer Sheath** | Black |


RoHS
RoHS