


YSLYCY 0,6/1 KV SHIELDED PVC CONTROL CABLE

KAB600104015/04

YSLYCY-JZ 4G1,5 mm² 0,6/1 kV musta


- Oil resistant
- Flexible
- Numbered wires
- Good EMC-properties

PRODUCT DESCRIPTION

YSLYCY 0,6/1 kV control and connection cable is suitable for multitude of applications in various industries, such as machining tools, automotive industry, CNC-routers and packaging machines. In order to achieve the optimal EMC-properties the copper screen has to be grounded.

SPECIFICATIONS

Number Of leads	4
Cross-Section	1.5 mm ²
Material Outer Jacket	PVC
Shielded	Yes
Nominal Voltage	Uo/U 0,6/1 kV
Diameter Outer -5%	12.2 mm
Temperature Range The Use Of	-40 °C
Temperature Range For Flexible Use	70 °C
Temperature Range Flexible Use Of	-10 °C
Bending Radius Fixed Laying	Min. 10 x d
Bending Radius Flexible Use	Min. 10 x d
Copper Weight	104 kg/km
Weight	240 kg/km
Core Insulation	PVC
Core identification	Number Coded
Approvals	RoHS
Test Voltage	4000 V
Area of application	Flexible use
Colour Outer Sheath	Black

RRRC