

HMH/HMH-EB HALOGEN-FREE CONTROL CABLE

SAB62000740/04K HMH-JZ 7G4 mm²

| 4OEM | ALITO | MATIC |
|--------|-------|--------|
| 10LIVI | AUIU | WIATIC |

| 1 |
|--------|
| |
| Ц. |

- Numbered cores
- Flame retardant and self-extinguishing
- Flexible
- · Easy stripping

PRODUCT DESCRIPTION

HMH/HMH-EB is a halogen-free control cable constructed for use as control, measuring and monitoring cable in multitude of applications such as assembly lines and conveyor belts. Suitable for dry and damp environments as well as areas prone to fire.

SPECIFICATIONS

| Number Of leads | 7 |
|------------------------------|----------------|
| Cross-Section | 4 mm² |
| Material Outer Jacket | LSZH |
| Shielded | No |
| Nominal Voltage | Uo/U 300/500 V |
| Diameter Outer -5% | 16 mm |
| Temperature Range The Use Of | -40 °C |
| Copper Weight | 406 kg/km |
| Weight | 403 kg/km |
| Core identification | Number Coded |
| Approvals | RoHS |
| Halogen | Yes |
| Halogen free | Yes |
| Colour Outer Sheath | Grey |

##