

HMH-C HALOGEN-FREE CONTROL CABLE

SAB62380210/04K HMH-C-OZ 2x1 mm²



| | ı |
|---|---|
| | |
| | |
| | |
| ı | |
| | |
| ı | |
| | |
| ı | |
| | |
| | |
| | |
| l | |
| | |
| ı | |
| | |
| | |
| | I |
| | |
| | |
| | |
| | |
| | |
| | l |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| ı | |
| l | |
| | |
| | |
| ı | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| ı | |
| l | |
| | |
| ı | |
| l | |
| l | |
| | |
| | |
| ı | |
| l | |
| | |
| | |
| ı | |
| | |
| | |
| | |
| ı | |
| | |
| | |

- Numbered cores
- · Good EMC properties
- Flexible
- Flame retardant and self-extinguishing

PRODUCT DESCRIPTION

HMH-C is a halogen-free control cable constructed for use as control, measuring and monitoring cable in multitude of applications such as assembly lines and conveyor belts. Suitable for dry and damp environments as well as areas prone to fire. Overall copper screen for EMC characteristics.

SPECIFICATIONS

| Number Of leads | 2 |
|------------------------------|----------------|
| Cross-Section | 1 mm² |
| Material Outer Jacket | LSZH |
| Shielded | Yes |
| Nominal Voltage | Uo/U 300/500 V |
| Diameter Outer -5% | 8.4 mm |
| Temperature Range The Use Of | -40 °C |
| Copper Weight | 51 kg/km |
| Weight | 58 kg/km |
| Core identification | Number Coded |
| Approvals | RoHS |
| Halogen | Yes |
| Halogen free | Yes |
| Colour Outer Sheath | Grey |

