


YSLCY PVC CONTROL CABLE

SAB02380510/04K
 YSLCY-JZ 5G1 mm²

- Numbered cords
- Good EMC properties
- Flexible
- Small outer diameter and bend radius



PRODUCT DESCRIPTION

Suitable to be used as control and connection cable for example in automotive industry and automation applications as well as press machines, textile, printing and paper machines. PVC insulation substituted with PET tape. In order to achieve optimal EMC properties the copper screen has to be grounded.

SPECIFICATIONS

| | |
|------------------------------------|-------------------|
| Number Of leads | 5 |
| Cross-Section | 1 mm ² |
| Material Outer Jacket | PVC |
| Shielded | Yes |
| Nominal Voltage | Uo/U 300/500 V |
| Diameter Outer -5% | 7.8 mm |
| Temperature Range The Use Of | -40 °C |
| Temperature Range For Flexible Use | 70 °C |
| Temperature Range Flexible Use Of | -5 °C |
| Bending Radius Fixed Laying | Min. 10 x d |
| Bending Radius Flexible Use | Min. 10 x d |
| Copper Weight | 71.2 kg/km |
| Weight | 104 kg/km |
| Core Insulation | PVC |
| Core identification | Number Coded |
| Approvals | RoHS |
| Test Voltage | 3000 V |
| Area of application | Flexible use |
| Colour Outer Sheath | Grey |

