


## YSLYCY SHIELDED PVC CONTROL CABLE

SAB02440205/04K  
YSLYCY-OZ 2x0,5 mm<sup>2</sup>



- Flexible
- Numbered wires
- Good EMC properties

### PRODUCT DESCRIPTION

YSLYCY control and connection cable is suitable for multitude of applications in various industries, such as machining tools, automotive industry, CNC-routers and packaging machines. In order to achieve the optimal EMC-properties the copper screen has to be grounded.

## SPECIFICATIONS

Number Of leads	2
Cross-Section	0.5 mm <sup>2</sup>
Material Outer Jacket	PVC
Shielded	Yes
Nominal Voltage	U <sub>o</sub> /U 300/500 V
Diameter Outer -5%	7.5 mm
Temperature Range The Use Of	-40 °C
Temperature Range For Flexible Use	80 °C
Temperature Range Flexible Use Of	-5 °C
Bending Radius Fixed Laying	Min. 7,5 x d
Bending Radius Flexible Use	Min. 7,5 x d
Copper Weight	30 kg/km
Weight	74 kg/km
Core Insulation	PVC
Core identification	Number Coded
Approvals	RoHS
Test Voltage	4000 V
Area of application	Flexible use
Colour Outer Sheath	Transparent