


## YSLYCY 0,6/1 KV SHIELDED PVC CONTROL CABLE

KAB600103010/04K  
 YSLYCY-JZ 3G1 mm<sup>2</sup> 0,6/1kV



- Oil resistant
- Flexible
- Numbered wires
- Good EMC-properties

### PRODUCT DESCRIPTION

YSLYCY 0,6/1 kV control and connection cable is suitable for multitude of applications in various industries, such as machining tools, automotive industry, CNC-routers and packaging machines. In order to achieve the optimal EMC-properties the copper screen has to be grounded.

### SPECIFICATIONS

|                                    |                   |
|------------------------------------|-------------------|
| Number Of leads                    | 3                 |
| Cross-Section                      | 1 mm <sup>2</sup> |
| Material Outer Jacket              | PVC               |
| Shielded                           | Yes               |
| Nominal Voltage                    | Uo/U 0,6/1 kV     |
| Diameter Outer -5%                 | 9.8 mm            |
| Temperature Range The Use Of       | -40 °C            |
| Temperature Range For Flexible Use | 70 °C             |
| Temperature Range Flexible Use Of  | -10 °C            |
| Bending Radius Fixed Laying        | Min. 10 x d       |
| Bending Radius Flexible Use        | Min. 10 x d       |
| Copper Weight                      | 67 kg/km          |
| Weight                             | 163 kg/km         |
| Core Insulation                    | PVC               |
| Core identification                | Number Coded      |
| Approvals                          | RoHS              |
| Test Voltage                       | 4000 V            |
| Area of application                | Flexible use      |
| Colour Outer Sheath                | Black             |

**RRRC**