


## 2YSLCYK-J 0,6/1 KV

KAB55000467/04K

2YSLCYK-J 4G95 mm<sup>2</sup> 0,6/1kV


- Shielded
- Motor power supply cable
- Good EMC-properties

### PRODUCT DESCRIPTION

2YSLCYK-J 0,6/1 kV motor power supply cable is suitable for frequency converters. In order to achieve optimal EMC-properties the copper screen has to be grounded.

### SPECIFICATIONS

|                                    |                            |
|------------------------------------|----------------------------|
| Number Of leads                    | 4                          |
| Cross-Section                      | 95 mm <sup>2</sup>         |
| Material Outer Jacket              | PVC                        |
| Shielded                           | Yes                        |
| Nominal Voltage                    | U <sub>0</sub> /U 0,6/1 kV |
| Rated voltage U <sub>0</sub> / U   | 0,6/1kV                    |
| Diameter Outer -5%                 | 46 mm                      |
| Temperature Range The Use Of       | -40 °C                     |
| Temperature Range For Flexible Use | 70 °C                      |
| Temperature Range Flexible Use Of  | -5 °C                      |
| Copper Weight                      | 4316 kg/km                 |
| Weight                             | 5300 kg/km                 |
| Core Insulation                    | PVC                        |
| Core identification                | Colour Coded               |
| Approvals                          | RoHS                       |
| Test Voltage                       | 2500 V                     |
| Area of application                | Flexible use               |
| Colour Outer Sheath                | Black                      |

**RRRR**