


## 2YSLCYK-J 0,6/1 KV

KAB55000360/04K

2YSLCYK-J 3x6+3G1 mm<sup>2</sup> 0,6/1kV


- Shielded
- Motor power supply cable
- Good EMC-properties

### PRODUCT DESCRIPTION

2YSLCYK-J 0,6/1 kV motor power supply cable is suitable for frequency converters. In order to achieve optimal EMC-properties the copper screen has to be grounded.

### SPECIFICATIONS

|                                                   |                            |
|---------------------------------------------------|----------------------------|
| Material Outer Jacket                             | PVC                        |
| Shielded                                          | Yes                        |
| Nominal Voltage                                   | U <sub>o</sub> /U 0,6/1 kV |
| Rated voltage U <sub>0</sub> / U                  | 0,6/1kV                    |
| Diameter Outer -5%                                | 15 mm                      |
| Temperature Range The Use Of                      | -40 °C                     |
| Temperature Range For Flexible Use                | 70 °C                      |
| Temperature Range Flexible Use Of                 | -5 °C                      |
| Copper Weight                                     | 298 kg/km                  |
| Weight                                            | 376 kg/km                  |
| Core Insulation                                   | PVC                        |
| Core identification                               | Colour Coded               |
| Approvals                                         | RoHS                       |
| Test Voltage                                      | 2500 V                     |
| Area of application                               | Flexible use               |
| Colour Outer Sheath                               | Black                      |
| Number of cores and cross-section mm <sup>2</sup> | 3x6+3G1 mm <sup>2</sup>    |

**RRRC**