

## LIYY PVC ELECTRONIC CABLE

SAB03052034/04K  
 LIYY 20x0,34 mm<sup>2</sup>129



- Color coded according to DIN 47100
- Flexible
- Small outer diameter
- Small bend radius

### PRODUCT DESCRIPTION

LIYY PVC electronic cable is suitable for use in industrial applications such as scales and control panels to transmit measuring, control and voice signals.

### SPECIFICATIONS

|                                    |                                                                                |
|------------------------------------|--------------------------------------------------------------------------------|
| Number Of leads                    | 20                                                                             |
| Cross-Section                      | 0.34 mm <sup>2</sup>                                                           |
| Material Outer Jacket              | PVC                                                                            |
| Shielded                           | No                                                                             |
| Nominal Voltage                    | U <sub>0</sub> /U 0,14 mm <sup>2</sup> = 350 V, ≥ 0,25 mm <sup>2</sup> = 500 V |
| Diameter Outer -5%                 | 9.5 mm                                                                         |
| Temperature Range The Use Of       | -40 °C                                                                         |
| Temperature Range For Flexible Use | 80 °C                                                                          |
| Temperature Range Flexible Use Of  | -5 °C                                                                          |
| Copper Weight                      | 59 kg/km                                                                       |
| Weight                             | 135 kg/km                                                                      |
| Core Insulation                    | PVC                                                                            |
| Core identification                | Colour Coded                                                                   |
| Approvals                          | RoHS                                                                           |
| Test Voltage                       | 2000 V                                                                         |
| Area of application                | Flexible use                                                                   |
| Colour Outer Sheath                | Grey                                                                           |