

H05RN-F FINE-STRANDED CABLE

KAB01000207/04K
H05RN-F 2x0,75 mm²



- Rubber cable for connecting electrical appliances
- Suited for low mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Dry, damp and wet areas
- Withstands fat and oils

PRODUCT DESCRIPTION

H05RN-F is a rubber cable suitable for connecting various electrical appliances as well as fixed installations. Suitable for dry, damp and wet environments and areas where the cable comes in contact with fat and oils. Also withstands ozone and low mechanical stress.

SPECIFICATIONS

| | |
|------------------------------------|------------------------|
| Number Of leads | 2 |
| Cross-Section | 0.75 mm ² |
| Material Outer Jacket | Rubber compound |
| Nominal Voltage | Uo/U 300/500 V |
| Diameter Outer -5% | 8.2 mm |
| Temperature Range The Use Of | -30 °C |
| Temperature Range For Flexible Use | 60 °C |
| Temperature Range Flexible Use Of | -30 °C |
| Bending Radius Fixed Laying | Min. 7,5 x d |
| Bending Radius Flexible Use | Min. 7,5 x d |
| Copper Weight | 14.4 kg/km |
| Weight | 63 kg/km |
| Core Insulation | Rubber compound |
| Core identification | Colour Coded |
| Approvals | RoHS |
| Test Voltage | 2000 V |
| Area of application | Flexible use |
| Drag Chain Tested | No |
| Colour Outer Sheath | Black |
| Cable type | Rubber-insulated cable |

RRcRRc