

H05RN-F FINE-STRANDED CABLE

KAB01000307/04K

H05RN-F 3G0,75 mm²


- Rubber cable for connecting electrical appliances
- Suited for low mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Dry, damp and wet areas
- Withstands fat and oils

PRODUCT DESCRIPTION

H05RN-F is a rubber cable suitable for connecting various electrical appliances as well as fixed installations. Suitable for dry, damp and wet environments and areas where the cable comes in contact with fat and oils. Also withstands ozone and low mechanical stress.

SPECIFICATIONS

Number Of leads	3
Cross-Section	0.75 mm ²
Material Outer Jacket	Rubber compound
Nominal Voltage	Uo/U 300/500 V
Diameter Outer -5%	7.8 mm
Temperature Range The Use Of	-30 °C
Temperature Range For Flexible Use	60 °C
Temperature Range Flexible Use Of	-30 °C
Bending Radius Fixed Laying	Min. 7,5 x d
Bending Radius Flexible Use	Min. 7,5 x d
Copper Weight	21.6 kg/km
Weight	77 kg/km
Core Insulation	Rubber compound
Core identification	Colour Coded
Approvals	RoHS
Test Voltage	2000 V
Area of application	Flexible use
Colour Outer Sheath	Black
Cable type	Rubber-insulated cable

RRRC