


## **H05RR-F FINE-STRANDED CABLE**

KAB00900207/04K H05RR-F 2x0,75 mm<sup>2</sup>



- Rubber cable for connecting electrical appliances
- · Suited for medium mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Household, office and commercial applications

## PRODUCT DESCRIPTION

Rubber-insulated H05RR-F is suitable for connecting various household, office and commercial electrical appliances such as vacuums, different kitchen equipment and tools. Withstands medium mechanical stress, applicable also for fixed installations.

## **SPECIFICATIONS**

Number Of leads	2
Cross-Section	0.75 mm²
Material Outer Jacket	Rubber compound
Shielded	No
Nominal Voltage	Uo/U 300/500 V
Diameter Outer -5%	6.2 mm
Temperature Range The Use Of	-30 °C
Temperature Range For Flexible Use	60 °C
Temperature Range Flexible Use Of	-30 °C
Bending Radius Fixed Laying	Min. 7,5 x d
Bending Radius Flexible Use	Min. 7,5 x d
Copper Weight	14.4 kg/km
Weight	51 kg/km
Core Insulation	Rubber compound
Core identification	Colour Coded
Approvals	RoHS
Test Voltage	2000 V
Area of application	Flexible use
Drag Chain Tested	No
Colour Outer Sheath	Black

