

H05RR-F FINE-STRANDED CABLE

KAB00900310/04K
H05RR-F 3G1 mm²



- Rubber cable for connecting electrical appliances
- Suited for medium mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Household, office and commercial applications

PRODUCT DESCRIPTION

Rubber-insulated H05RR-F is suitable for connecting various household, office and commercial electrical appliances such as vacuums, different kitchen equipment and tools. Withstands medium mechanical stress, applicable also for fixed installations.

SPECIFICATIONS

Number Of leads	3
Cross-Section	1 mm ²
Material Outer Jacket	Rubber compound
Shielded	No
Nominal Voltage	U _o /U 300/500 V
Diameter Outer -5%	9.2 mm
Temperature Range The Use Of	-30 °C
Temperature Range For Flexible Use	60 °C
Temperature Range Flexible Use Of	-30 °C
Bending Radius Fixed Laying	Min. 7,5 x d
Bending Radius Flexible Use	Min. 7,5 x d
Copper Weight	29 kg/km
Weight	73 kg/km
Core Insulation	Rubber compound
Core identification	Colour Coded
Approvals	RoHS
Test Voltage	2000 V
Area of application	Flexible use
Colour Outer Sheath	Black
Cable type	Rubber-insulated cable

RRcRRc