

## H05RR-F FINE-STRANDED CABLE

KAB00900425/04K  
H05RR-F 4G2,5 mm<sup>2</sup>



- Rubber cable for connecting electrical appliances
- Suited for medium mechanical stress
- Rubber insulation according to DIN VDE 0282 part 4
- Household, office and commercial applications

### PRODUCT DESCRIPTION

Rubber-insulated H05RR-F is suitable for connecting various household, office and commercial electrical appliances such as vacuums, different kitchen equipment and tools. Withstands medium mechanical stress, applicable also for fixed installations.

### SPECIFICATIONS

Number Of leads	4
Cross-Section	2.5 mm <sup>2</sup>
Material Outer Jacket	Rubber compound
Shielded	No
Nominal Voltage	U <sub>o</sub> /U 300/500 V
Diameter Outer -5%	14 mm
Temperature Range The Use Of	-30 °C
Temperature Range For Flexible Use	60 °C
Temperature Range Flexible Use Of	-30 °C
Bending Radius Fixed Laying	Min. 7,5 x d
Bending Radius Flexible Use	Min. 7,5 x d
Copper Weight	96 kg/km
Weight	216 kg/km
Core Insulation	Rubber compound
Core identification	Colour Coded
Approvals	RoHS
Test Voltage	2000 V
Area of application	Flexible use
Colour Outer Sheath	Black
Cable type	Rubber-insulated cable

**RRcRRc**