

SIHF SILICONE CABLE

SAB01410607/04K SIHF-J 6G0,75 mm²





- Heat resistant
- Flexible also in negative temperatures
- Suitable for use in various industries

PRODUCT DESCRIPTION

SIHF is a heat resistant control or connection cable spesifically constructed for demanding environments with fluctuating temperatures. Temperature range for mobile operation from -60°C up to +180°C. Must not be exposed to forced guidance.

Applicable for example in metal industry, foundries as well as glass, cement and ceramic manufacturing.

SPECIFICATIONS

| Number Of leads | 6 |
|--------------------------------------|----------------|
| Cross-Section | 0.75 mm² |
| Material Outer Jacket | Silicone |
| Shielded | No |
| Nominal Voltage | Uo/U 300/500 V |
| Diameter Outer -5% | 9.2 mm |
| Temperature Range The Use Of | -60 °C |
| Temperature Range For Flexible Use | 180 °C |
| Temperature Range Flexible Use Of | -60 °C |
| Copper Weight | 43 kg/km |
| Weight | 115 kg/km |
| Core Insulation | Silicone |
| Core identification | Number Coded |
| Approvals | RoHS |
| Test Voltage | 2000 V |
| Area of application | Flexible use |
| Colour Outer Sheath | Red-brown |
| Temperature Range For Short-Term Use | 250 °C |