

(N)GFLCGÖU SHIELDED RUBBER FLAT CABLE

Shielded

KAB003504250/04
(N)GFLCGÖU-J 4G25 mm²



- Neoprene sheathed
- Good EMC characteristics
- Flame retardant
- Oil resistant

PRODUCT DESCRIPTION

Flat control cable suitable for various applications such as hoists, transport equipment and cranes. Outer sheath made out of rubber compound, overall copper screen for good EMC characteristics.

Can be installed dry, damp or wet rooms as well as outdoors. The cable is resistant to oil and flame retardant in accordance with DIN EN 60332-1-2, IEC 60332-1

SPECIFICATIONS

| | |
|------------------------------------|--------------------|
| Number Of leads | 4 |
| Cross-Section | 25 mm ² |
| Material Outer Jacket | Rubber compound |
| Shielded | Yes |
| Nominal Voltage | 0,6/1 kV |
| Temperature Range The Use Of | -40 °C |
| Temperature Range For Flexible Use | 80 °C |
| Temperature Range Flexible Use Of | -30 °C |
| Bending Radius Fixed Laying | 5 x d |
| Bending Radius Flexible Use | 5 x d |
| Copper Weight | 1200 kg/km |
| Weight | 1605 kg/km |
| Core Insulation | Rubber compound |
| Core identification | Colour Coded |
| Approvals | RoHS |
| Test Voltage | 3500 V |
| Area of application | Flexible use |

Colour Outer Sheath

Black
