

STCN (EMC) SHIELDED LIFT CABLE

KAB012204010/04
STCN-JB 4x1 mm²



- Built-in suspension element
- Neopren sheathed

PRODUCT DESCRIPTION

Shielded STCN is a round neopren sheathed cable suitable for various applications in dry, damp and wet environments both in- and outdoors. For dynamic and fixed installations. Can be used for exable as control cable in elevators.

High resistance against oils, greases and chemicals.

SPECIFICATIONS

| | |
|------------------------------------|-------------------|
| Number Of leads | 4 |
| Cross-Section | 1 mm ² |
| Material Outer Jacket | Neoprene |
| Shielded | Yes |
| Nominal Voltage | Uo/U 450/750V |
| Diameter Outer -5% | 11.5 mm |
| Temperature Range The Use Of | -40 °C |
| Temperature Range For Flexible Use | 70 °C |
| Temperature Range Flexible Use Of | -30 °C |
| Bending Radius Fixed Laying | 10 x d |
| Bending Radius Flexible Use | 10 x d |
| Copper Weight | 74 kg/km |
| Weight | 176 kg/km |
| Core Insulation | Rubber compound |
| Core identification | Colour Coded |
| Approvals | RoHS |
| Test Voltage | 3000 V |
| Area of application | Flexible use |
| Colour Outer Sheath | Black |