

## KYSTY, KYSTUY-J LIFT CABLE

KAB014004007/04  
 KYSTY 4G0,75 mm<sup>2</sup>



- Built-in suspension element
- PVC sheathed

### PRODUCT DESCRIPTION

PVC sheathed control cable with suspension element in the center of the cable. Suitable for use as lift control cable in conveyors, machine tools and construction equipment.

Can be installed in dry or damp conditions, either mobile operation or fixed installation.

## SPECIFICATIONS

<b>Number Of leads</b>	4
<b>Cross-Section</b>	0.75 mm <sup>2</sup>
<b>Material Outer Jacket</b>	PVC
<b>Shielded</b>	No
<b>Nominal Voltage</b>	U <sub>0</sub> /U 300/500 V
<b>Diameter Outer -5%</b>	6.7 mm
<b>Temperature Range The Use Of</b>	-40 °C
<b>Temperature Range For Flexible Use</b>	40 °C
<b>Temperature Range Flexible Use Of</b>	-15 °C
<b>Bending Radius Fixed Laying</b>	10 x d
<b>Bending Radius Flexible Use</b>	10 x d
<b>Copper Weight</b>	33.6 kg/km
<b>Weight</b>	85 kg/km
<b>Core identification</b>	Number Coded
<b>Approvals</b>	RoHS
<b>Test Voltage</b>	3000 V
<b>Area of application</b>	Flexible use
<b>Drag Chain Tested</b>	No
<b>Colour Outer Sheath</b>	Black